



Vehicle Wrap Guidelines

Client should wash the vehicle on the day before installation using a normal wash with **no wax**. Dry outdoors and move the vehicle inside a **minimum of 12 hours before** the installation.

Client should provide an interior location for the installation with adequate lighting and a temperature between 60-80°F. If the outdoor temperature will fall below 50° overnight, a longer period may be required.

Vehicle must have an automotive grade paint finish. Surfaces with primer, rust or other forms of damage will result in difficulty with the installation, and will interfere with the adhesive.

If the finish is not in good condition as outlined above, the installed vinyl cannot be guaranteed by Cushing.

Vinyl cannot be installed to unpainted or primed surfaces, plastic bumpers, rubber or aluminum; nor to door moldings and handles.

Design template for the client's vehicle may vary from the actual vehicle due to changes in body, hardware or contours. All care will be given to ensure a good installation when the template does not match the vehicle.

Complicated areas, such as the curves behind door handles, may be wrapped with some patches. Patches should be noticeable only upon close inspection.

For emblems, client should specify if the installers are to wrap the vinyl on top of existing emblems, or remove the emblems. Removing emblems can cause minor scratching, and the emblems themselves are prone to break during removal. Cushing is not responsible for any vehicle or emblem damage caused by removal of emblems.

It is always our goal to provide the best possible result for our clients, and Cushing stands behind their work. If a difficulty presents during the installation, we will communicate with the client to explain the problem and reach a resolution so that the installation can proceed.

Once wrapped, please do not wash the car in automated car washes, as this may remove the vinyl, or cause blisters or peeling.